

Safety Data Sheet

according to Regulation (EC) No 1907/2006

8600/30N PU Resin

Revision date: 20.11.2024

Product code: 50032

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

8600/30N PU Resin

UFI: FGJF-643T-100E-E0VU

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Resins (prepolymers)

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Company name:	Kisling (Deutschland) GmbH	
Street:	Salzstraße 15	
Place:	D-74676 Niedernhall	
Telephone:	+49 7940 50961 61	
E-mail:	customerservice@kisling.com	
Contact person:	Product Compliance	Telephone: +49 7940 5096 143
E-mail:	compliance@kisling.com	
Internet:	www.kisling.com	

1.4. Emergency telephone number:

24 hr. emergency phone number +1 872 5888271 (KAR)
Medicines & Poisons Info Office +356 2545 6508

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin Sens. 1; H317

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

Fatty acids, C18-unsaturated, trimers, combination with oleylamine
Fatty acids, tall oil, compounds with oleylamine

Signal word: Warning

Pictograms:



Hazard statements

H317 May cause an allergic skin reaction.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P261	Avoid breathing Vapour.
P280	Wear protective gloves and eye protection/face protection.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

8600/30N PU Resin

Revision date: 20.11.2024

Product code: 50032

Page 2 of 12

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of substances listed below with nonhazardous components.

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
25791-96-2	Glycerine, propoxylated			5 - < 15 %
	Acute Tox. 4; H302			
147900-93-4	Fatty acids, C18-unsaturated, trimers, combination with oleylamine			0.1 - < 1 %
	604-612-4		01-2119971821-33	
	Acute Tox. 4, Skin Sens. 1, STOT RE 2, Aquatic Chronic 2; H302 H317 H373 H411			
85711-55-3	Fatty acids, tall oil, compounds with oleylamine			0.1 - < 1 %
	288-315-1		01-2119974148-28	
	Eye Dam. 1, Skin Sens. 1A, STOT RE 2; H318 H317 H373			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
25791-96-2		Glycerine, propoxylated	5 - < 15 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 1000 mg/kg	
147900-93-4	604-612-4	Fatty acids, C18-unsaturated, trimers, combination with oleylamine	0.1 - < 1 %
		oral: LD50 = > 1570 mg/kg	
85711-55-3	288-315-1	Fatty acids, tall oil, compounds with oleylamine	0.1 - < 1 %
		oral: LD50 = > 2000 mg/kg	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No special measures are necessary.

After inhalation

Provide fresh air.

After contact with skin

Gently wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.

After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. IF SWALLOWED: Immediately call a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Irritant — skin irritation and eye damage

May cause respiratory irritation. Dyspnoea.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

8600/30N PU Resin

Revision date: 20.11.2024

Product code: 50032

Page 3 of 12

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO₂), Dry extinguishing powder

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products, Flammable vapours can accumulate in steam space of closed systems.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. Evacuate area.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Use personal protection equipment. See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers). Retain contaminated washing water and dispose it. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

For cleaning up

Soak up inert absorbent and dispose as waste requiring special attention.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas. Keep away from sources of ignition - No smoking.

Avoid contact with skin, eyes and clothes. People who suffer from skin sensitization problems, asthma, allergies, chronic or recurring respiratory illnesses should not be deployed in any process using this mixture.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

Further information on handling

Keep only in the original container in a cool, well-ventilated place.

Never use pressure to empty container. Do not allow to enter into surface water or drains.

7.2. Conditions for safe storage, including any incompatibilities

Safety Data Sheet

according to Regulation (EC) No 1907/2006

8600/30N PU Resin

Revision date: 20.11.2024

Product code: 50032

Page 4 of 12

Requirements for storage rooms and vessels

Keep container tightly closed and in a well-ventilated place.

Hints on joint storage

No special measures are necessary.

Further information on storage conditions

No special measures are necessary.

7.3. Specific end use(s)

Resins (prepolymers)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

CAS No	Name of agent		
DNEL type	Exposure route	Effect	Value
25791-96-2	Glycerine, propoxylated		
Worker DNEL, long-term	inhalation	systemic	98 mg/m ³
Worker DNEL, long-term	dermal	systemic	13,9 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	29 mg/m ³
Consumer DNEL, long-term	dermal	systemic	8,3 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	8,3 mg/kg bw/day
147900-93-4	Fatty acids, C18-unsaturated, trimers, combination with oleylamine		
Worker DNEL, long-term	dermal	systemic	0,024 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	0,012 mg/kg bw/day
Consumer DNEL, long-term	dermal	systemic	0,012 mg/kg bw/day
85711-55-3	Fatty acids, tall oil, compounds with oleylamine		
Consumer DNEL, long-term	oral	systemic	0,012 mg/kg bw/day
Worker DNEL, long-term	dermal	systemic	0,024 mg/kg bw/day
Consumer DNEL, long-term	dermal	systemic	0,012 mg/kg bw/day

Safety Data Sheet

according to Regulation (EC) No 1907/2006

8600/30N PU Resin

Revision date: 20.11.2024

Product code: 50032

Page 5 of 12

PNEC values

CAS No	Name of agent	Value
Environmental compartment		
25791-96-2	Glycerine, propoxylated	
Freshwater		0,2 mg/l
Freshwater (intermittent releases)		1 mg/l
Marine water		0,02 mg/l
Freshwater sediment		0,52 mg/kg
Marine sediment		0,052 mg/kg
Micro-organisms in sewage treatment plants (STP)		1000 mg/l
Soil		0,067 mg/kg
147900-93-4	Fatty acids, C18-unsaturated, trimers, combination with oleylamine	
Freshwater		0,006 mg/l
Marine water		0,0006 mg/l
Freshwater sediment		2,46 mg/l
Marine sediment		0,25 mg/l
Secondary poisoning		0,47 mg/kg
Soil		0,28 mg/kg
85711-55-3	Fatty acids, tall oil, compounds with oleylamine	
Secondary poisoning		0,47 mg/kg

Additional advice on limit values

To date, no national critical limit values exist.

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection.

Hand protection

Wear protective gloves.

Breakthrough times and swelling properties of the material must be taken into consideration.

NBR (Nitrile rubber) 0,4 mm, Breakthrough time: 480 min

EN ISO 374

Skin protection

Avoid contact with skin, eyes and clothes.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Do not allow to enter into surface water or drains.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

8600/30N PU Resin

Revision date: 20.11.2024

Product code: 50032

Page 6 of 12

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	beige
Odour:	characteristic
Odour threshold:	not determined

Test method

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	>200 °C
Flammability:	not applicable
Lower explosion limits:	not determined
Upper explosion limits:	not determined
Flash point:	>100 °C
Auto-ignition temperature:	not determined
Decomposition temperature:	not determined
pH-Value:	not determined
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.
Solubility in other solvents	not determined
Partition coefficient n-octanol/water:	not determined
Vapour pressure:	not determined
Density (at 22 °C):	0,94 - 0,98 g/cm ³ DIN EN ISO 2811
Relative vapour density:	not determined

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

The product is not: Explosive.

Oxidizing properties

The product is not: oxidising.

Other safety characteristics

Evaporation rate:	not determined
Solid content:	not determined
Viscosity / dynamic: (at 22 °C)	300-700 mPa·s DIN 53019

SECTION 10: Stability and reactivity

10.1. Reactivity

No known hazardous reactions.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Thermal decomposition can lead to the escape of irritating gases and vapours.

Vapours can form explosive mixtures with air.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

8600/30N PU Resin

Revision date: 20.11.2024

Product code: 50032

Page 7 of 12

10.4. Conditions to avoid

No information available.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicokinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) 4000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
25791-96-2	Glycerine, propoxylated				
	oral	LD50 > 1000 mg/kg	Rat	Pre-supplier/manufacturer	OECD 423
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1992)	OECD Guideline 402
147900-93-4	Fatty acids, C18-unsaturated, trimers, combination with oleylamine				
	oral	LD50 > 1570 mg/kg	Rat	Pre-supplier/manufacturer	OECD 423
85711-55-3	Fatty acids, tall oil, compounds with oleylamine				
	oral	LD50 > 2000 mg/kg	Rat	Study report (2011)	OECD Guideline 423

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (Fatty acids, C18-unsaturated, trimers, combination with oleylamine; Fatty acids, tall oil, compounds with oleylamine)

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

8600/30N PU Resin

Revision date: 20.11.2024

Product code: 50032

Page 8 of 12

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

No data available

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

May be harmful if swallowed, in contact with skin or if inhaled.

11.2. Information on other hazards

Other information

No data available

Further information

No data available

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
25791-96-2	Glycerine, propoxylated					
	Acute fish toxicity	LC50 > 1000 mg/l	96 h	Leuciscus idus	Study report (1992)	OECD Guideline 203
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Desmodesmus subspicatus	Study report (2003)	EU Method C.3
	Acute crustacea toxicity	EC50 > 100 mg/l	48 h	Daphnia magna	Study report (1992)	OECD Guideline 202
	Crustacea toxicity	NOEC >= 10 mg/l	21 d	Daphnia magna	Study report (2005)	OECD Guideline 211
	Acute bacteria toxicity	EC50 >10000 mg/l ()	3 h	Activated sludge	Pre-supplier/manufacturer	
147900-93-4	Fatty acids, C18-unsaturated, trimers, combination with oleylamine					
	Acute fish toxicity	LL50 >100 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	Pre-supplier/manufacturer	OECD 203
	Acute crustacea toxicity	EL50 >100 mg/l	48 h	Daphnia magna (Big water flea)	Pre-supplier/manufacturer	OECD 202
	Acute bacteria toxicity	EC50 >1000 mg/l ()	3 h	Activated sludge	Pre-supplier/manufacturer	OECD 209
85711-55-3	Fatty acids, tall oil, compounds with oleylamine					
	Acute fish toxicity	LL50 >100 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	Pre-supplier/manufacturer	OECD 203
	Acute crustacea toxicity	EL50 15,2 mg/l	48 h	Daphnia magna (Big water flea)	Pre-supplier/manufacturer	OECD 202
	Acute bacteria toxicity	EC50 >1000 mg/l ()	3 h	Activated sludge	Pre-supplier/manufacturer	OECD 209

Safety Data Sheet

according to Regulation (EC) No 1907/2006

8600/30N PU Resin

Revision date: 20.11.2024

Product code: 50032

Page 9 of 12

12.2. Persistence and degradability

No data available

CAS No	Chemical name	Method	Value	d	Source
		Evaluation			
147900-93-4	Fatty acids, C18-unsaturated, trimers, combination with oleylamine				
	OECD 301F, aerob	27%	28	Pre-supplier/manufactur er	
	Moderately/partially biodegradable.				
85711-55-3	Fatty acids, tall oil, compounds with oleylamine				
	OECD 301F, aerob	87%	28	Pre-supplier/manufactur er	
	Readily biodegradable (according to OECD criteria).				

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
25791-96-2	Glycerine, propoxylated	>= -1,82 - 12
147900-93-4	Fatty acids, C18-unsaturated, trimers, combination with oleylamine	>5,7
85711-55-3	Fatty acids, tall oil, compounds with oleylamine	> 6,2

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Safety Data Sheet

according to Regulation (EC) No 1907/2006

8600/30N PU Resin

Revision date: 20.11.2024

Product code: 50032

Page 10 of 12

List of Wastes Code - contaminated packaging

150102 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); plastic packaging

Contaminated packaging

Completely emptied packages can be recycled. Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
14.4. Packing group: No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
14.4. Packing group: No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
14.4. Packing group: No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
14.4. Packing group: No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

Information according to Directive 2012/18/EU (SEVESO III):

Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D):

2 - obviously hazardous to water

Skin resorption/Sensitization:

Causes allergic hypersensitivity reactions.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

8600/30N PU Resin

Revision date: 20.11.2024

Product code: 50032

Page 11 of 12

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

Acute Tox: Acute toxicity

Eye Dam: Eye damage

Skin Sens: Skin sensitisation

STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Chronic: Chronic aquatic hazard

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

CAS: Chemical Abstracts Service

DNEL: Derived No Effect Level

DMEL: Derived Minimal Effect Level

PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

LL50: Lethal loading, 50%

EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate

NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic

vPvB: very persistent, very bioaccumulative

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

IMDG: International Maritime Code for Dangerous Goods

EmS: Emergency Schedules

MFAG: Medical First Aid Guide

IATA: International Air Transport Association

ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container

SVHC: Substance of Very High Concern

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Skin Sens. 1; H317	Calculation method

Relevant H and EUH statements (number and full text)

H302 Harmful if swallowed.
H317 May cause an allergic skin reaction.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

8600/30N PU Resin

Revision date: 20.11.2024

Product code: 50032

Page 12 of 12

H318	Causes serious eye damage.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)