

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 1663 - Component A 1665

Revision date: 21.03.2025

Product code: 1663

Page 1 of 23

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Kisling - 1663 - Component A 1665

UFI: 4SK4-V0ME-800D-VW08

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Adhesives and sealants

#### Uses advised against

No information available.

### 1.3. Details of the supplier of the safety data sheet

#### Manufacturer

Company name:	Kisling AG	
Street:	Motorenstrasse 102	
Place:	CH-8620 Wetzikon	
Telephone:	+41 58 272 0 272	
E-mail:	customerservice@kisling.com	
Contact person:	Product Compliance	Telephone: +49 7940 5096 143
E-mail:	compliance@kisling.com	
Internet:	www.kisling.com	

#### Supplier

Company name:	Kisling (Deutschland) GmbH	
Street:	Salzstraße 15	
Place:	D-74676 Niedernhall	
Telephone:	+49 7940 50961 61	
E-mail:	customerservice@kisling.com	
Contact person:	Product Compliance	Telephone: +49 7940 5096 143
E-mail:	compliance@kisling.com	
Internet:	www.kisling.com	

**1.4. Emergency telephone number:** 24 hr. emergency phone number +1 872 5888271 (KAR)  
Medicines & Poisons Info Office +356 2545 6508

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Regulation (EC) No 1272/2008

Flam. Sol. 1; H228  
Acute Tox. 4; H332  
Skin Irrit. 2; H315  
Eye Dam. 1; H318  
Skin Sens. 1; H317  
STOT SE 3; H335

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

#### Regulation (EC) No 1272/2008

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 1663 - Component A 1665

Revision date: 21.03.2025

Product code: 1663

Page 2 of 23

#### Hazard components for labelling

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate  
[2-(Methacryloyloxy)-ethyl]-hydrogen succinate  
methacrylic acid; 2-methylpropenoic acid  
Propylidynetrimethanol, ethoxylated, esters with acrylic acid  
Bis(methacryloyloxyethyl) hydrogen phosphate  
2-hydroxyethyl methacrylate  
@000000000779  
tributylamine

**Signal word:** Danger

**Pictograms:**



#### Hazard statements

H228 Flammable solid.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.

#### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P280 Wear protective gloves and eye protection/face protection.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 Immediately call a POISON CENTER/doctor.

#### Labelling of packages where the contents do not exceed 125 ml

**Signal word:** Danger

**Pictograms:**



#### Hazard statements

H317-H318

#### Precautionary statements

P280-P305+P351+P338-P310

#### 2.3. Other hazards

No data available

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Chemical characterization

Mixture of substances listed below with nonhazardous components.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 1663 - Component A 1665

Revision date: 21.03.2025

Product code: 1663

Page 3 of 23

#### Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate			30 - < 50 %
	201-297-1	607-035-00-6		
	Flam. Liq. 2, Skin Irrit. 2, Skin Sens. 1, STOT SE 3; H225 H315 H317 H335			
20882-04-6	[2-(Methacryloyloxy)-ethyl]-hydrogen succinate			5 - < 15 %
	244-096-4			
	Eye Dam. 1, Skin Sens. 1A; H318 H317			
79-41-4	methacrylic acid; 2-methylpropenoic acid			1 - < 5 %
	201-204-4	607-088-00-5	01-2119463884-26	
	Acute Tox. 3, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1A, Eye Dam. 1, STOT SE 3; H311 H332 H302 H314 H318 H335			
28961-43-5	Propylidynetrimethanol, ethoxylated, esters with acrylic acid			0.1 - < 1 %
	500-066-5		01-2119489900-30	
	Eye Irrit. 2, Skin Sens. 1B, Aquatic Chronic 3; H319 H317 H412			
32435-46-4	Bis(methacryloyloxyethyl) hydrogen phosphate			0.1 - < 1 %
	251-040-2			
	Eye Dam. 1, Skin Sens. 1B; H318 H317			
868-77-9	2-hydroxyethyl methacrylate			0.1 - < 1 %
	212-782-2	607-124-00-X	01-2119490169-29	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1; H315 H319 H317			
103671-44-9	N,N-bis-(2-hydroxyethyl)-para-toluidine			0.1 - < 1 %
	911-490-9		01-2119979579-10	
	Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Skin Sens. 1, Aquatic Chronic 3; H302 H315 H318 H317 H412			
102-82-9	tributylamine			0.1 - < 1 %
	203-058-7			
	Acute Tox. 1, Acute Tox. 2, Acute Tox. 4, Skin Irrit. 2; H330 H310 H302 H315			
99-97-8	N,N-dimethyl-p-toluidine			0.1 - < 1 %
	202-805-4	612-056-00-9	01-2119956633-31	
	Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, STOT RE 2, Aquatic Chronic 3; H331 H311 H301 H373 H412			
26741-53-7	3,9-bis(2,4-di-tert-butylphenoxy)-2,4,8,10-tetraoxa-3,9-diphosphaspiro[5.5]undecane			0.1 - < 1 %
	247-952-5			
	Aquatic Chronic 1; H410			
106-51-4	p-benzoquinone; quinone			< 0.1 %
	203-405-2	606-013-00-3		
	Acute Tox. 3, Acute Tox. 3, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, Aquatic Acute 1; H331 H301 H315 H319 H335 H400			
123-31-9	1,4-dihydroxybenzene; hydroquinone; quinol			< 0.1 %
	204-617-8	604-005-00-4	01-2119524016-51	
	Carc. 2, Muta. 2, Acute Tox. 4, Eye Dam. 1, Skin Sens. 1B, Aquatic Acute 1, Aquatic Chronic 1; H351 H341 H302 H318 H317 H400 H410			

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 1663 - Component A 1665

Revision date: 21.03.2025

Product code: 1663

Page 4 of 23

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
80-62-6	201-297-1	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate	30 - < 50 %
		inhalation: LC50 = 29,8 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = ca. 7900 mg/kg	
20882-04-6	244-096-4	[2-(Methacryloyloxy)-ethyl]-hydrogen succinate	5 - < 15 %
		oral: LD50 = > 2000 mg/kg	
79-41-4	201-204-4	methacrylic acid; 2-methylpropenoic acid	1 - < 5 %
		inhalation: LC50 = 7,1 mg/l (vapours); inhalation: ATE = 1.5 mg/l (dusts or mists); dermal: LD50 = 500 mg/kg; oral: LD50 = 1320 mg/kg Eye Dam. 1; H318: >= 3 - 100 Eye Irrit. 2; H319: >= - < 3 STOT SE 3; H335: >= 1 - 100	
28961-43-5	500-066-5	Propylidynetrimethanol, ethoxylated, esters with acrylic acid	0.1 - < 1 %
		dermal: LD50 = > 13200 mg/kg; oral: LD50 = > 2000 mg/kg	
868-77-9	212-782-2	2-hydroxyethyl methacrylate	0.1 - < 1 %
		oral: LD50 = 5050 mg/kg	
103671-44-9	911-490-9	N,N-bis-(2-hydroxyethyl)-para-toluidine	0.1 - < 1 %
		oral: ATE = 500 mg/kg	
102-82-9	203-058-7	tributylamine	0.1 - < 1 %
		inhalation: LC50 = 0,5 mg/l (vapours); inhalation: ATE = 0.005 mg/l (dusts or mists); dermal: LD50 = 195 mg/kg; oral: LD50 = 420 mg/kg	
99-97-8	202-805-4	N,N-dimethyl-p-toluidine	0.1 - < 1 %
		inhalation: ATE = 3 mg/l (vapours); inhalation: ATE = 0.5 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: ATE = 100 mg/kg	
26741-53-7	247-952-5	3,9-bis(2,4-di-tert-butylphenoxy)-2,4,8,10-tetraoxa-3,9-diphosphaspiro[5.5]undecane	0.1 - < 1 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg Aquatic Chronic 1; H410: M=1	
106-51-4	203-405-2	p-benzoquinone; quinone	< 0.1 %
		inhalation: ATE = 3 mg/l (vapours); inhalation: ATE = 0.5 mg/l (dusts or mists); oral: LD50 = 197 mg/kg Aquatic Acute 1; H400: M=10	
123-31-9	204-617-8	1,4-dihydroxybenzene; hydroquinone; quinol	< 0.1 %
		oral: LD50 = 302 mg/kg Aquatic Acute 1; H400: M=10 Aquatic Chronic 1; H410: M=1	

#### SECTION 4: First aid measures

##### 4.1. Description of first aid measures

###### General information

No special measures are necessary.

###### After inhalation

Provide fresh air.

###### After contact with skin

Gently wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.

###### After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. IF SWALLOWED: Immediately call a doctor.

##### 4.2. Most important symptoms and effects, both acute and delayed

Irritant — skin irritation and eye damage

May cause respiratory irritation. Dyspnoea.

##### 4.3. Indication of any immediate medical attention and special treatment needed

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 1663 - Component A 1665

Revision date: 21.03.2025

Product code: 1663

Page 5 of 23

Treat symptomatically.

#### SECTION 5: Firefighting measures

##### 5.1. Extinguishing media

###### **Suitable extinguishing media**

alcohol resistant foam, Carbon dioxide (CO<sub>2</sub>), Dry extinguishing powder

###### **Unsuitable extinguishing media**

Full water jet.

##### 5.2. Special hazards arising from the substance or mixture

Hazardous combustion products, Flammable vapours can accumulate in steam space of closed systems.

##### 5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

##### **Additional information**

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. Evacuate area.

#### SECTION 6: Accidental release measures

##### 6.1. Personal precautions, protective equipment and emergency procedures

###### **General advice**

Use personal protection equipment. See protective measures under point 7 and 8.

##### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

##### 6.3. Methods and material for containment and cleaning up

###### **For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers). Retain contaminated washing water and dispose it. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

###### **For cleaning up**

Soak up inert absorbent and dispose as waste requiring special attention.

##### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

#### SECTION 7: Handling and storage

##### 7.1. Precautions for safe handling

###### **Advice on safe handling**

Use only in well-ventilated areas. Keep away from sources of ignition - No smoking.

Avoid contact with skin, eyes and clothes. People who suffer from skin sensitization problems, asthma, allergies, chronic or recurring respiratory illnesses should not be deployed in any process using this mixture.

###### **Advice on general occupational hygiene**

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

###### **Further information on handling**

Keep only in the original container in a cool, well-ventilated place.

Never use pressure to empty container. Do not allow to enter into surface water or drains.

##### 7.2. Conditions for safe storage, including any incompatibilities

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 1663 - Component A 1665

Revision date: 21.03.2025

Product code: 1663

Page 6 of 23

#### Requirements for storage rooms and vessels

Keep container tightly closed and in a well-ventilated place.

#### Hints on joint storage

No special measures are necessary.

#### Further information on storage conditions

No special measures are necessary.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Occupational exposure limit values

CAS No	Name of agent	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
80-62-6	Methyl methacrylate	50	-		TWA (8 h)	
		100	-		STEL (15 min)	

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 1663 - Component A 1665

Revision date: 21.03.2025

Product code: 1663

Page 7 of 23

#### DNEL/DMEL values

CAS No	Name of agent	Exposure route	Effect	Value
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate			
Worker DNEL, long-term		inhalation	systemic	348,4 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	local	208 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	local	416 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	13,67 mg/kg bw/day
Worker DNEL, long-term		dermal	local	1,5 mg/cm <sup>2</sup>
Worker DNEL, acute		dermal	local	1,5 mg/cm <sup>2</sup>
Consumer DNEL, long-term		inhalation	systemic	74,3 mg/m <sup>3</sup>
Consumer DNEL, long-term		inhalation	local	104 mg/m <sup>3</sup>
Consumer DNEL, acute		inhalation	local	208 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	8,2 mg/kg bw/day
Consumer DNEL, long-term		dermal	local	1,5 mg/cm <sup>2</sup>
Consumer DNEL, acute		dermal	local	1,5 mg/cm <sup>2</sup>
Consumer DNEL, long-term		oral	systemic	8,2 mg/kg bw/day
79-41-4	methacrylic acid; 2-methylpropenoic acid			
Worker DNEL, long-term		inhalation	systemic	39,3 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	local	44 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	4,25 mg/kg bw/day
Worker DNEL, long-term		dermal	local	0,38 mg/cm <sup>2</sup>
Consumer DNEL, long-term		inhalation	systemic	11,7 mg/m <sup>3</sup>
Consumer DNEL, long-term		inhalation	local	8,8 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	5,35 mg/kg bw/day
Consumer DNEL, long-term		dermal	local	0,23 mg/cm <sup>2</sup>
Consumer DNEL, long-term		oral	systemic	5,35 mg/kg bw/day
28961-43-5	Propylidynetrimethanol, ethoxylated, esters with acrylic acid			
Worker DNEL, long-term		inhalation	systemic	37 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	10,5 mg/kg bw/day
102-82-9	tributylamine			
Worker DNEL, long-term		inhalation	systemic	5,3 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	systemic	10,6 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	local	15,2 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	local	15,2 mg/m <sup>3</sup>
99-97-8	N,N-dimethyl-p-toluidine			
Worker DNEL, long-term		inhalation	systemic	0,128 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	0,624 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,336 mg/m <sup>3</sup>

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 1663 - Component A 1665

Revision date: 21.03.2025

Product code: 1663

Page 8 of 23

Consumer DNEL, long-term	dermal	systemic	0,223 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	0,02 mg/kg bw/day
26741-53-7	3,9-bis(2,4-di-tert-butylphenoxy)-2,4,8,10-tetraoxa-3,9-diphosphaspiro[5.5]undecane		
Worker DNEL, long-term	inhalation	systemic	2,75 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic	0,78 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	0,68 mg/m <sup>3</sup>
Consumer DNEL, long-term	dermal	systemic	0,39 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	0,39 mg/kg bw/day
123-31-9	1,4-dihydroxybenzene; hydroquinone; quinol		
Worker DNEL, long-term	inhalation	systemic	2,1 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic	3,33 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	1,05 mg/m <sup>3</sup>
Consumer DNEL, long-term	dermal	systemic	1,66 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	0,6 mg/kg bw/day

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 1663 - Component A 1665

Revision date: 21.03.2025

Product code: 1663

Page 9 of 23

#### PNEC values

CAS No	Name of agent	Value
Environmental compartment		
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate	
Freshwater		0,94 mg/l
Freshwater (intermittent releases)		0,69 mg/l
Marine water		0,094 mg/l
Freshwater sediment		10,2 mg/kg
Marine sediment		1,02 mg/kg
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		1,48 mg/kg
79-41-4	methacrylic acid; 2-methylpropenoic acid	
Freshwater		0,82 mg/l
Freshwater (intermittent releases)		0,45 mg/l
Marine water		0,082 mg/l
Freshwater sediment		3,09 mg/kg
Marine sediment		0,309 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		0,137 mg/kg
28961-43-5	Propylidynetrimethanol, ethoxylated, esters with acrylic acid	
Freshwater		0,002 mg/l
Freshwater (intermittent releases)		0,019 mg/l
Marine water		0 mg/l
Freshwater sediment		0,038 mg/kg
Marine sediment		0,004 mg/kg
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		0,006 mg/kg
102-82-9	tributylamine	
Freshwater		0,008 mg/l
Freshwater (intermittent releases)		0,08 mg/l
Marine water		0,0008 mg/l
Freshwater sediment		35,85 mg/kg
Marine sediment		3,59 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		7,17 mg/kg
99-97-8	N,N-dimethyl-p-toluidine	
Freshwater		0,153 mg/l
Freshwater (intermittent releases)		0,153 mg/l
Marine water		0,015 mg/l
Freshwater sediment		45,378 mg/kg
Marine sediment		45,378 mg/kg
Micro-organisms in sewage treatment plants (STP)		4,286 mg/l
Soil		18,677 mg/kg

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 1663 - Component A 1665

Revision date: 21.03.2025

Product code: 1663

Page 10 of 23

26741-53-7	3,9-bis(2,4-di-tert-butylphenoxy)-2,4,8,10-tetraoxa-3,9-diphosphaspiro[5.5]undecane	
Freshwater		0,002 mg/l
Freshwater (intermittent releases)		0,707 mg/l
Marine water		0 mg/l
Freshwater sediment		2000000 mg/kg
Marine sediment		200000 mg/kg
Micro-organisms in sewage treatment plants (STP)		42 mg/l
Soil		1 mg/kg
123-31-9	1,4-dihydroxybenzene; hydroquinone; quinol	
Freshwater		0,00057 mg/l
Freshwater (intermittent releases)		0,00134 mg/l
Marine water		0,000057 mg/l
Freshwater sediment		0,0049 mg/kg
Marine sediment		0,00049 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,71 mg/l
Soil		0,00064 mg/kg

#### 8.2. Exposure controls



##### Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

##### Individual protection measures, such as personal protective equipment

###### Eye/face protection

Wear eye/face protection.

###### Hand protection

Wear protective gloves.

Breakthrough times and swelling properties of the material must be taken into consideration.

NBR (Nitrile rubber) 0,4 mm, Breakthrough time: 480 min

EN ISO 374

###### Skin protection

Avoid contact with skin, eyes and clothes.

###### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

###### Environmental exposure controls

Do not allow to enter into surface water or drains.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Paste
Colour:	beige
Odour:	characteristic
Odour threshold:	not determined

Melting point/freezing point:

Test method  
not determined

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 1663 - Component A 1665

Revision date: 21.03.2025

Product code: 1663

Page 11 of 23

Boiling point or initial boiling point and boiling range:	not determined
Flammability:	not determined not applicable
Lower explosion limits:	not determined
Upper explosion limits:	not determined
Flash point:	27 °C ISO 3679
Auto-ignition temperature:	not determined
Decomposition temperature:	not determined
pH-Value:	not determined
Viscosity / kinematic:	not determined
Water solubility:	practically insoluble
Solubility in other solvents not determined	
Partition coefficient n-octanol/water:	not determined
Vapour pressure:	not determined
Density (at 20 °C):	0.99 g/cm <sup>3</sup>
Relative density:	not determined
Relative vapour density:	not determined
Particle characteristics:	Polymer preparations and compounds Particle size < 5 mm

#### 9.2. Other information

##### Information with regard to physical hazard classes

Explosive properties

The product is not: Explosive.

Oxidizing properties

not determined

##### Other safety characteristics

Evaporation rate:

not determined

Solid content:

not determined

Viscosity / dynamic:  
(at 25 °C)

175.000 mPa·s

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No known hazardous reactions.

### 10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

### 10.3. Possibility of hazardous reactions

Thermal decomposition can lead to the escape of irritating gases and vapours.

Vapours can form explosive mixtures with air.

### 10.4. Conditions to avoid

No information available.

### 10.5. Incompatible materials

No information available.

### 10.6. Hazardous decomposition products

No known hazardous decomposition products.

### Further information

No data available

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 1663 - Component A 1665

Revision date: 21.03.2025

Product code: 1663

Page 12 of 23

#### SECTION 11: Toxicological information

##### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

###### **Toxicokinetics, metabolism and distribution**

No data available

###### **Acute toxicity**

Harmful if inhaled.

###### **ATEmix calculated**

ATE (oral) > 5000 mg/kg; ATE (dermal) > 5000 mg/kg; ATE (inhalation vapour) > 50 mg/l; ATE (inhalation dust/mist) 1.211 mg/l

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 1663 - Component A 1665

Revision date: 21.03.2025

Product code: 1663

Page 13 of 23

CAS No	Chemical name					
	Exposure route	Dose	Species	Source	Method	
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate					
	oral	LD50 mg/kg	ca. 7900	Rat	J. Ind. Hyg. Toxicol. 23: 343-351 (1941)	Study to assess the acute oral toxicity
	dermal	LD50 mg/kg	> 5000	Rabbit	Study report (1982)	OECD Guideline 402
	inhalation (4 h) vapour	LC50	29,8 mg/l	Rat	J. Dent. Res. 59: 1074 (1980)	Study to assess the acute inhalative tox
20882-04-6	[2-(Methacryloyloxy)-ethyl]-hydrogen succinate					
	oral	LD50 mg/kg	> 2000	Rat	Study report (2016)	OECD Guideline 423
79-41-4	methacrylic acid; 2-methylpropenoic acid					
	oral	LD50 mg/kg	1320	Rat	Study report (1977)	OECD Guideline 401
	dermal	LD50 mg/kg	500	Rabbit	Pre-supplier/manufac turer	
	inhalation (4 h) vapour	LC50	7,1 mg/l	Rat	Pre-supplier/manufac turer	OECD 403
	inhalation dust/mist	ATE	1.5 mg/l			
28961-43-5	Propylidynetrimethanol, ethoxylated, esters with acrylic acid					
	oral	LD50 mg/kg	> 2000	Rat	Study report (1998)	OECD Guideline 401
	dermal	LD50 mg/kg	> 13200	Rabbit	Study report (1984)	An acute dermal toxicity study was perfo
868-77-9	2-hydroxyethyl methacrylate					
	oral	LD50 mg/kg	5050	Rat		
103671-44-9	N,N-bis-(2-hydroxyethyl)-para-toluidine					
	oral	ATE mg/kg	500			
102-82-9	tributylamine					
	oral	LD50 mg/kg	420	Rat	Publication (1974)	Method: acute oral toxicity test Screeni
	dermal	LD50 mg/kg	195	Rabbit	Publication (1974)	Method: acute dermal toxicity Screening
	inhalation (4 h) vapour	LC50	0,5 mg/l	Rat	Study report (1987)	OECD Guideline 403
	inhalation dust/mist	ATE mg/l	0.005			
99-97-8	N,N-dimethyl-p-toluidine					
	oral	ATE mg/kg	100			
	dermal	ATE mg/kg	300			
	inhalation vapour	ATE	3 mg/l			
	inhalation dust/mist	ATE	0.5 mg/l			

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 1663 - Component A 1665

Revision date: 21.03.2025

Product code: 1663

Page 14 of 23

26741-53-7	3,9-bis(2,4-di-tert-butylphenoxy)-2,4,8,10-tetraoxa-3,9-diphosphaspiro[5.5]undecane				
	oral	LD50 mg/kg	> 5000	Rat	Study report (1984) OECD Guideline 401
	dermal	LD50 mg/kg	> 2000	Rabbit	Study report (1994) OECD Guideline 402
106-51-4	p-benzoquinone; quinone				
	oral	LD50 mg/kg	197	Rat	Study report (2017) OECD Guideline 423
	inhalation vapour	ATE	3 mg/l		
	inhalation dust/mist	ATE	0.5 mg/l		
123-31-9	1,4-dihydroxybenzene; hydroquinone; quinol				
	oral	LD50 mg/kg	302	Rat	IUCLID

#### Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye damage.

#### Sensitising effects

May cause an allergic skin reaction. (methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; [2-(Methacryloyloxy)-ethyl]-hydrogen succinate; Propylidynetrimethanol, ethoxylated, esters with acrylic acid; Bis(methacryloyloxyethyl) hydrogen phosphate; 2-hydroxyethyl methacrylate; N,N-bis-(2-hydroxyethyl)-para-toluidine; 1,4-dihydroxybenzene; hydroquinone; quinol)

#### Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

#### STOT-single exposure

May cause respiratory irritation. (methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methacrylic acid; 2-methylpropenoic acid)

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### Information on likely routes of exposure

No data available

#### Specific effects in experiment on an animal

No data available

#### Additional information on tests

No data available

#### Practical experience

May be harmful if swallowed, in contact with skin or if inhaled.

#### 11.2. Information on other hazards

##### Other information

No data available

##### Further information

No data available

### SECTION 12: Ecological information

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 1663 - Component A 1665

Revision date: 21.03.2025

Product code: 1663

Page 15 of 23

#### 12.1. Toxicity

Based on available data, the classification criteria are not met.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 1663 - Component A 1665

Revision date: 21.03.2025

Product code: 1663

Page 16 of 23

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate					
	Acute fish toxicity	LC50 > 79 mg/l	96 h	Oncorhynchus mykiss	REACH Registration Dossier	EPA OTS 797.1400
	Acute algae toxicity	ErC50 > 110 mg/l	72 h	Raphidocelis subcapitata	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EC50 69 mg/l	48 h	Daphnia magna	REACH Registration Dossier	EPA OTS 797.1300
	Fish toxicity	NOEC 9,4 mg/l	35 d	Danio rerio	REACH Registration Dossier	OECD Guideline 210
	Crustacea toxicity	NOEC 37 mg/l	21 d	Daphnia magna	REACH Registration Dossier	OECD Guideline 211
	Acute bacteria toxicity	EC50 3162 mg/l ( )	3 h	Activated sludge	Publication (2008)	ISO 8192
20882-04-6	[2-(Methacryloyloxy)-ethyl]-hydrogen succinate					
	Acute algae toxicity	ErC50 >= 197 mg/l	72 h	Pseudokirchneriella subcapitata	Study report (2016)	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 515,4 mg/l	48 h	Daphnia magna	Study report (2016)	OECD Guideline 202
	Algae toxicity	NOEC >= 197 mg/l	3 d	Pseudokirchneriella subcapitata	Pre-supplier/manufacturer	OECD 201
	Crustacea toxicity	NOEC > 515,4 mg/l	2 d	Daphnia magna	Pre-supplier/manufacturer	OECD 202
79-41-4	methacrylic acid; 2-methylpropenoic acid					
	Acute fish toxicity	LC50 85 mg/l	96 h	Oncorhynchus mykiss	REACH Registration Dossier	EPA OTS 797.1400
	Acute algae toxicity	ErC50 45 mg/l	72 h	Raphidocelis subcapitata	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 130 mg/l	48 h	Daphnia magna	REACH Registration Dossier	EPA OTS 797.1300
	Fish toxicity	NOEC 10 mg/l	35 d	Danio rerio	REACH Registration Dossier	OECD Guideline 210
	Crustacea toxicity	NOEC 53 mg/l	21 d	Daphnia magna	REACH Registration Dossier	OECD Guideline 211
	Acute bacteria toxicity	EC50 13500 mg/l ( )	3 h	Activated sludge	Publication (2008)	ISO 8192
28961-43-5	Propylidynetrimethanol, ethoxylated, esters with acrylic acid					

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 1663 - Component A 1665

Revision date: 21.03.2025

Product code: 1663

Page 17 of 23

	Acute fish toxicity	LC50 mg/l	1,95	96 h	Danio rerio	REACH Registration Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50	2,2 mg/l	72 h	Desmodesmus subspicatus	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	70,7	48 h	Daphnia magna	REACH Registration Dossier	OECD Guideline 202
868-77-9	2-hydroxyethyl methacrylate						
	Acute fish toxicity	LC50	227 mg/l	96 h	Pimephales promelas		
102-82-9	tributylamine						
	Acute fish toxicity	LC50 mg/l	16,3	96 h	Oryzias latipes	Study report (2000)	other: Testing Methods for Industrial Wa
	Acute algae toxicity	ErC50 mg/l	10,1	72 h	Raphidocelis subcapitata	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EC50	8 mg/l	48 h	Daphnia magna (Big water flea)	Pre-supplier/man ufacturer	OECD 202
99-97-8	N,N-dimethyl-p-toluidine						
	Acute fish toxicity	LC50 mg/l	52,8	96 h	Pimephales promelas	REACH Registration Dossier	other: Standard test procedure ASTM, 198
	Acute algae toxicity	ErC50 mg/l	23,69	72 h	Raphidocelis subcapitata	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	15,27	48 h	Daphnia magna	REACH Registration Dossier	other: Modeling database
	Acute bacteria toxicity	EC50 ( )	100 mg/l	3 h	WoE 2. domestic activated sludge, WoE 3. Pseudomon	REACH Registration Dossier	other: as mentioned below
26741-53-7	3,9-bis(2,4-di-tert-butylphenoxy)-2,4,8,10-tetraoxa-3,9-diphosphaspiro[5.5]undecane						
	Acute fish toxicity	LC50 mg/l	70,7	96 h	Danio rerio	Study report (2013)	OECD Guideline 203
	Acute algae toxicity	ErC50	97 mg/l	72 h	Desmodesmus subspicatus	Study report (2013)	OECD Guideline 201
	Crustacea toxicity	NOEC	0,1 mg/l	21 d	Daphnia magna	Study report (2013)	OECD Guideline 211
	Acute bacteria toxicity	EC50 mg/l ( )	> 1000	3 h	activated sludge, domestic	Study report (2012)	OECD Guideline 209
106-51-4	p-benzoquinone; quinone						
	Acute algae toxicity	ErC50	1.5 mg/l	72 h	Desmodesmus subspicatus	Study report (2018)	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	0.13	48 h	Daphnia magna	Study report (2018)	OECD Guideline 202

#### 12.2. Persistence and degradability

No data available

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 1663 - Component A 1665

Revision date: 21.03.2025

Product code: 1663

Page 18 of 23

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
20882-04-6	[2-(Methacryloyloxy)-ethyl]-hydrogen succinate			
	aerobic	>80%	28	Pre-supplier/manufactur er
	Readily biodegradable (according to OECD criteria).			
102-82-9	tributylamine			
	OECD 301B	88 %	28	Pre-supplier/manufactur er
	Readily biodegradable (according to OECD criteria).			
26741-53-7	3,9-bis(2,4-di-tert-butylphenoxy)-2,4,8,10-tetraoxa-3,9-diphosphaspiro[5.5]undecane			
	Activated sludge, Concentration: 31 mg/l	<10%	28	Pre-supplier/manufactur er
	Not readily biodegradable (according to OECD criteria)			

#### 12.3. Bioaccumulative potential

No data available

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate	1,38
20882-04-6	[2-(Methacryloyloxy)-ethyl]-hydrogen succinate	0,782
79-41-4	methacrylic acid; 2-methylpropenoic acid	0,93
28961-43-5	Propylidynetrimethanol, ethoxylated, esters with acrylic acid	2,89
868-77-9	2-hydroxyethyl methacrylate	0,47
102-82-9	tributylamine	3,338
99-97-8	N,N-dimethyl-p-toluidine	2,81
26741-53-7	3,9-bis(2,4-di-tert-butylphenoxy)-2,4,8,10-tetraoxa-3,9-diphosphaspiro[5.5]undecane	10,9
106-51-4	p-benzoquinone; quinone	>= 0.1 - = 4.8

#### BCF

CAS No	Chemical name	BCF	Species	Source
102-82-9	tributylamine	7,3	Cyprinus carpio	REACH Registration D
99-97-8	N,N-dimethyl-p-toluidine	33	Fish	REACH Registration D
26741-53-7	3,9-bis(2,4-di-tert-butylphenoxy)-2,4,8,10-tetraoxa-3,9-diphosphaspiro[5.5]undecane	0,89		SAR and QSAR in Envi

#### 12.4. Mobility in soil

No data available

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

No data available

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 1663 - Component A 1665

Revision date: 21.03.2025

Product code: 1663

Page 19 of 23

#### Disposal recommendations

Dispose of waste according to applicable legislation.

#### List of Wastes Code - residues/unused products

080410 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants other than those mentioned in 08 04 09

#### List of Wastes Code - used product

080410 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants other than those mentioned in 08 04 09

#### List of Wastes Code - contaminated packaging

080410 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants other than those mentioned in 08 04 09

#### Contaminated packaging

Completely emptied packages can be recycled. Dispose of waste according to applicable legislation.

### SECTION 14: Transport information

#### Land transport (ADR/RID)

**14.1. UN number or ID number:** UN 3175  
**14.2. UN proper shipping name:** SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (METHYL METHACRYLATE)  
**14.3. Transport hazard class(es):** 4.1  
**14.4. Packing group:** II  
Hazard label: 4.1



Classification code: F1  
Special Provisions: 216 274 601  
Limited quantity: 1 kg  
Excepted quantity: E2  
Transport category: 2  
Hazard No: 40  
Tunnel restriction code: E

#### Inland waterways transport (ADN)

**14.1. UN number or ID number:** UN 3175  
**14.2. UN proper shipping name:** SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (METHYL METHACRYLATE)  
**14.3. Transport hazard class(es):** 4.1  
**14.4. Packing group:** II  
Hazard label: 4.1



Classification code: F1

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 1663 - Component A 1665

Revision date: 21.03.2025

Product code: 1663

Page 20 of 23

Special Provisions: 216 274 601 800  
 Limited quantity: 1 kg  
 Excepted quantity: E2

#### Marine transport (IMDG)

**14.1. UN number or ID number:** UN 3175  
**14.2. UN proper shipping name:** SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (METHYL METHACRYLATE)  
**14.3. Transport hazard class(es):** 4.1  
**14.4. Packing group:** II  
 Hazard label: 4.1



Special Provisions: 216 274  
 Limited quantity: 1 kg  
 Excepted quantity: E2  
 EmS: F-A, S-I

#### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number or ID number:** UN 3175  
**14.2. UN proper shipping name:** SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (METHYL METHACRYLATE)  
**14.3. Transport hazard class(es):** 4.1  
**14.4. Packing group:** II  
 Hazard label: 4.1



Special Provisions: A46  
 Limited quantity Passenger: 5 kg  
 Passenger LQ: Y441  
 Excepted quantity: E2  
 IATA-packing instructions - Passenger: 445  
 IATA-max. quantity - Passenger: 15 kg  
 IATA-packing instructions - Cargo: 448  
 IATA-max. quantity - Cargo: 50 kg

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

#### 14.6. Special precautions for user

No information available.

#### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

#### Other applicable information

1663+1664  
 UN 3527 = POLYESTER RESIN KIT, solid base material, Class 4.1, II

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 1663 - Component A 1665

Revision date: 21.03.2025

Product code: 1663

Page 21 of 23

Restrictions on use (REACH, annex XVII):

Entry 40, Entry 75

Directive 2010/75/EU on industrial emissions: 52.689 % (521.62 g/l)

Information according to Directive 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

#### National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

#### SECTION 16: Other information

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 1663 - Component A 1665

Revision date: 21.03.2025

Product code: 1663

Page 22 of 23

#### Abbreviations and acronyms

Flam. Liq: Flammable liquid  
Flam. Sol: Flammable solid  
Acute Tox: Acute toxicity  
Skin Corr: Skin corrosion  
Skin Irrit: Skin irritation  
Eye Dam: Eye damage  
Eye Irrit: Eye irritation  
Skin Sens: Skin sensitisation  
Muta: Germ cell mutagenicity  
Carc: Carcinogenicity  
STOT SE: Specific target organ toxicity - single exposure  
STOT RE: Specific target organ toxicity - repeated exposure  
Aquatic Acute: Acute aquatic hazard  
Aquatic Chronic: Chronic aquatic hazard  
CLP: Classification, labelling and Packaging  
REACH: Registration, Evaluation and Authorization of Chemicals  
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals  
UN: United Nations  
CAS: Chemical Abstracts Service  
DNEL: Derived No Effect Level  
DMEL: Derived Minimal Effect Level  
PNEC: Predicted No Effect Concentration  
ATE: Acute toxicity estimate  
LC50: Lethal concentration, 50%  
LD50: Lethal dose, 50%  
LL50: Lethal loading, 50%  
EL50: Effect loading, 50%  
EC50: Effective Concentration 50%  
ErC50: Effective Concentration 50%, growth rate  
NOEC: No Observed Effect Concentration  
BCF: Bio-concentration factor  
PBT: persistent, bioaccumulative, toxic  
vPvB: very persistent, very bioaccumulative  
ADR: Accord européen sur le transport des marchandises dangereuses par Route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road )  
RID: Regulations concerning the international carriage of dangerous goods by rail  
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)  
IMDG: International Maritime Code for Dangerous Goods  
EmS: Emergency Schedules  
MFAG: Medical First Aid Guide  
IATA: International Air Transport Association  
ICAO: International Civil Aviation Organization  
MARPOL: International Convention for the Prevention of Marine Pollution from Ships  
IBC: Intermediate Bulk Container  
VOC: Volatile Organic Compounds  
SVHC: Substance of Very High Concern

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 1663 - Component A 1665

Revision date: 21.03.2025

Product code: 1663

Page 23 of 23

#### Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Sol. 1; H228	On basis of test data
Acute Tox. 4; H332	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1; H317	Calculation method
STOT SE 3; H335	Calculation method

#### Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H228	Flammable solid.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

#### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*