

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 5634

Revision date: 21.03.2025

Product code: 5634

Page 1 of 12

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Kisling - 5634

UFI: WQKG-R0GT-H00K-NH0F

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Adhesives and sealants

#### Uses advised against

No information available.

### 1.3. Details of the supplier of the safety data sheet

#### Manufacturer

|                 |                             |                              |
|-----------------|-----------------------------|------------------------------|
| Company name:   | Kisling AG                  |                              |
| Street:         | Motorenstrasse 102          |                              |
| Place:          | CH-8620 Wetzikon            |                              |
| Telephone:      | +41 58 272 0 272            |                              |
| E-mail:         | customerservice@kisling.com |                              |
| Contact person: | Product Compliance          | Telephone: +49 7940 5096 143 |
| E-mail:         | compliance@kisling.com      |                              |
| Internet:       | www.kisling.com             |                              |

#### Supplier

|                 |                             |                              |
|-----------------|-----------------------------|------------------------------|
| Company name:   | Kisling (Deutschland) GmbH  |                              |
| Street:         | Salzstraße 15               |                              |
| Place:          | D-74676 Niedernhall         |                              |
| Telephone:      | +49 7940 50961 61           |                              |
| E-mail:         | customerservice@kisling.com |                              |
| Contact person: | Product Compliance          | Telephone: +49 7940 5096 143 |
| E-mail:         | compliance@kisling.com      |                              |
| Internet:       | www.kisling.com             |                              |

**1.4. Emergency telephone number:** 24 hr. emergency phone number +1 872 5888271 (KAR)  
Medicines & Poisons Info Office +356 2545 6508

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Regulation (EC) No 1272/2008

Skin Irrit. 2; H315  
Eye Irrit. 2; H319  
STOT SE 3; H335

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

#### Regulation (EC) No 1272/2008

#### Hazard components for labelling

ethyl 2-cyanoacrylate

**Signal word:** Warning

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 5634

Revision date: 21.03.2025

Product code: 5634

Page 2 of 12

#### Pictograms:



#### Hazard statements

- H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.

#### Precautionary statements

- P261 Avoid breathing Vapour.  
P280 Wear protective gloves and eye protection/face protection.  
P302+P352 IF ON SKIN: Wash with plenty of water.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P312 Call a POISON CENTER/doctor if you feel unwell.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

#### Special labelling of certain mixtures

- EUH202 Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.

#### Labelling of packages where the contents do not exceed 125 ml

Signal word: Warning

#### Pictograms:



#### 2.3. Other hazards

No information available.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Chemical characterization

Mixture of substances listed below with nonhazardous components.

##### Relevant ingredients

| CAS No    | Chemical name                                                                                                                     |              |                  | Quantity     |
|-----------|-----------------------------------------------------------------------------------------------------------------------------------|--------------|------------------|--------------|
|           | EC No                                                                                                                             | Index No     | REACH No         |              |
|           | Classification (Regulation (EC) No 1272/2008)                                                                                     |              |                  |              |
| 7085-85-0 | ethyl 2-cyanoacrylate                                                                                                             |              |                  | 50 - < 100 % |
|           | 230-391-5                                                                                                                         | 607-236-00-9 | 01-2119527766-29 |              |
|           | Skin Irrit. 2, Eye Irrit. 2, STOT SE 3; H315 H319 H335                                                                            |              |                  |              |
| 123-31-9  | 1,4-dihydroxybenzene; hydroquinone; quinol                                                                                        |              |                  | < 0.1 %      |
|           | 204-617-8                                                                                                                         | 604-005-00-4 | 01-2119524016-51 |              |
|           | Carc. 2, Muta. 2, Acute Tox. 4, Eye Dam. 1, Skin Sens. 1B, Aquatic Acute 1, Aquatic Chronic 1; H351 H341 H302 H318 H317 H400 H410 |              |                  |              |

Full text of H and EUH statements: see section 16.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 5634

Revision date: 21.03.2025

Product code: 5634

Page 3 of 12

#### Specific Conc. Limits, M-factors and ATE

| CAS No    | EC No     | Chemical name                                                                       | Quantity     |
|-----------|-----------|-------------------------------------------------------------------------------------|--------------|
|           |           | Specific Conc. Limits, M-factors and ATE                                            |              |
| 7085-85-0 | 230-391-5 | ethyl 2-cyanoacrylate                                                               | 50 - < 100 % |
|           |           | dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg STOT SE 3; H335: >= 10 - 100 |              |
| 123-31-9  | 204-617-8 | 1,4-dihydroxybenzene; hydroquinone; quinol                                          | < 0.1 %      |
|           |           | oral: LD50 = 302 mg/kg Aquatic Acute 1; H400: M=10<br>Aquatic Chronic 1; H410: M=1  |              |

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

Never give anything by mouth to an unconscious person or a person with cramps.

If unconscious but breathing normally, place in recovery position and seek medical advice.

#### After inhalation

Remove casualty to fresh air and keep warm and at rest.

#### After contact with skin

Damage can be caused through mechanical influence of the product (eg. sticking).

Do not pull apart bonded skin areas. They can be carefully separated with a blunt object after soaking in warm soapy water. Cyanoacrylates release heat as they cure. In rare cases, a large amount of product can produce enough heat to cause burns. After the adhesive has been removed from the skin, the burns should be treated as ordinary burns. If the lips are accidentally glued together, apply warm water to the lips, ensure maximum wetting with saliva, and apply pressure from inside the mouth. Peel or roll the lips until they come apart. Do not try to pull the lips apart with opposing movements.

#### After contact with eyes

If the eye is so glued that it cannot be opened, loosen the eyelashes with warm water by applying a wet cotton pad. Cyanoacrylate hardens on the eye protein, causing tear flow. This helps to dissolve the adhesive again. Keep the eye covered until the adhesive is completely detached, which usually takes 1 to 3 days. Do not force the eye open. Seek medical attention if solid particles of cyanoacrylate are trapped under the lid and cause injury through friction.

#### After ingestion

Ensure that the airways are clear. The product polymerizes immediately in the mouth, making it almost impossible to swallow. Saliva slowly separates the hardened product from the mouth (several hours).

### 4.2. Most important symptoms and effects, both acute and delayed

Irritation to respiratory tract, Cough, Dyspnoea

Causes eye irritation. Conjunctival redness.

Causes skin irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. No further relevant information available.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Powder.

#### Unsuitable extinguishing media

No information available.

### 5.2. Special hazards arising from the substance or mixture

Danger of serious damage to health by prolonged exposure.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 5634

Revision date: 21.03.2025

Product code: 5634

Page 4 of 12

Use appropriate respiratory protection.

#### **5.3. Advice for firefighters**

Use water spray jet to protect personnel and to cool endangered containers.

Wear a self-contained breathing apparatus and chemical protective clothing.

#### **Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

#### **General advice**

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.

Use personal protection equipment. Provide adequate ventilation. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

### **6.2. Environmental precautions**

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

### **6.3. Methods and material for containment and cleaning up**

#### **For cleaning up**

Wash with plenty of water. Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

### **6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## **SECTION 7: Handling and storage**

### **7.1. Precautions for safe handling**

#### **Advice on safe handling**

Avoid contact with skin, eyes and clothes. Ventilate affected area.

#### **Advice on protection against fire and explosion**

No special fire protection measures are necessary.

#### **Advice on general occupational hygiene**

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

#### **Further information on handling**

Keep only in the original container in a cool, well-ventilated place.

### **7.2. Conditions for safe storage, including any incompatibilities**

#### **Requirements for storage rooms and vessels**

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations.

#### **Hints on joint storage**

none

#### **Further information on storage conditions**

Store in a cool dry place. Protect from direct sunlight.

### **7.3. Specific end use(s)**

Adhesives and sealants

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 5634

Revision date: 21.03.2025

Product code: 5634

Page 5 of 12

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### DNEL/DMEL values

| CAS No                   | Name of agent                              |                |          |                        |
|--------------------------|--------------------------------------------|----------------|----------|------------------------|
| DNEL type                |                                            | Exposure route | Effect   | Value                  |
| 7085-85-0                | ethyl 2-cyanoacrylate                      |                |          |                        |
| Worker DNEL, long-term   |                                            | inhalation     | systemic | 9,25 mg/m <sup>3</sup> |
| Worker DNEL, acute       |                                            | inhalation     | systemic | 9,25 mg/m <sup>3</sup> |
| Worker DNEL, long-term   |                                            | inhalation     | local    | 9,25 mg/m <sup>3</sup> |
| Worker DNEL, acute       |                                            | inhalation     | local    | 9,25 mg/m <sup>3</sup> |
| Consumer DNEL, long-term |                                            | inhalation     | systemic | 9,25 mg/m <sup>3</sup> |
| Consumer DNEL, acute     |                                            | inhalation     | systemic | 9,25 mg/m <sup>3</sup> |
| Consumer DNEL, long-term |                                            | inhalation     | local    | 9,25 mg/m <sup>3</sup> |
| Consumer DNEL, acute     |                                            | inhalation     | local    | 9,25 mg/m <sup>3</sup> |
| 123-31-9                 | 1,4-dihydroxybenzene; hydroquinone; quinol |                |          |                        |
| Worker DNEL, long-term   |                                            | inhalation     | systemic | 2,1 mg/m <sup>3</sup>  |
| Worker DNEL, long-term   |                                            | dermal         | systemic | 3,33 mg/kg bw/day      |
| Consumer DNEL, long-term |                                            | inhalation     | systemic | 1,05 mg/m <sup>3</sup> |
| Consumer DNEL, long-term |                                            | dermal         | systemic | 1,66 mg/kg bw/day      |
| Consumer DNEL, long-term |                                            | oral           | systemic | 0,6 mg/kg bw/day       |

#### PNEC values

| CAS No                                           | Name of agent                              |               |
|--------------------------------------------------|--------------------------------------------|---------------|
| Environmental compartment                        |                                            | Value         |
| 123-31-9                                         | 1,4-dihydroxybenzene; hydroquinone; quinol |               |
| Freshwater                                       |                                            | 0,00057 mg/l  |
| Freshwater (intermittent releases)               |                                            | 0,00134 mg/l  |
| Marine water                                     |                                            | 0,000057 mg/l |
| Freshwater sediment                              |                                            | 0,0049 mg/kg  |
| Marine sediment                                  |                                            | 0,00049 mg/kg |
| Micro-organisms in sewage treatment plants (STP) |                                            | 0,71 mg/l     |
| Soil                                             |                                            | 0,00064 mg/kg |

#### Additional advice on limit values

To date, no national critical limit values exist.

### 8.2. Exposure controls



#### Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 5634

Revision date: 21.03.2025

Product code: 5634

Page 6 of 12

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

#### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Wear eye/face protection.

##### Hand protection

Suitable material:

Thickness of the glove material >0,4 mm

> 480 min

See information supplied by the manufacturer.

##### Skin protection

Wear suitable protective clothing. The type of personal protection equipment has to be chosen based on the concentration and amount of the dangerous substance at the workplace.

##### Respiratory protection

In case of inadequate ventilation wear respiratory protection. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|                                                           |                |                        |
|-----------------------------------------------------------|----------------|------------------------|
| Physical state:                                           | Liquid         |                        |
| Colour:                                                   | colourless     |                        |
| Odour:                                                    | characteristic |                        |
| Odour threshold:                                          | not determined |                        |
| Melting point/freezing point:                             |                | not determined         |
| Boiling point or initial boiling point and boiling range: |                | >200 °C                |
| Flammability:                                             |                | not applicable         |
| Lower explosion limits:                                   |                | not determined         |
| Upper explosion limits:                                   |                | not determined         |
| Flash point:                                              |                | 80 °C                  |
| Auto-ignition temperature:                                |                | not determined         |
| Decomposition temperature:                                |                | not determined         |
| pH-Value:                                                 |                | not determined         |
| Viscosity / kinematic:                                    |                | not determined         |
| Water solubility:                                         |                | not determined         |
| Solubility in other solvents                              |                |                        |
| not determined                                            |                |                        |
| Partition coefficient n-octanol/water:                    |                | not determined         |
| Vapour pressure:                                          |                | not determined         |
| Density (at 20 °C):                                       |                | 1.04 g/cm <sup>3</sup> |
| Relative density:                                         |                | not determined         |
| Relative vapour density:                                  |                | not determined         |
| Particle characteristics:                                 |                | not determined         |

### 9.2. Other information

#### Information with regard to physical hazard classes

##### Explosive properties

The product is not: Explosive.

##### Oxidizing properties

not determined

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 5634

Revision date: 21.03.2025

Product code: 5634

Page 7 of 12

#### Other safety characteristics

Evaporation rate: not determined  
Solid content: not determined  
Viscosity / dynamic: 2400-2900 mPa·s  
(at 25 °C)

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Water, Amines, , Alcohol

#### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

#### 10.3. Possibility of hazardous reactions

No information available.

#### 10.4. Conditions to avoid

The product is chemically stable under recommended conditions of storage, use and temperature.

#### 10.5. Incompatible materials

No further relevant information available.

#### 10.6. Hazardous decomposition products

No further relevant information available.

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Toxicokinetics, metabolism and distribution

No data available

##### Acute toxicity

Based on available data, the classification criteria are not met.

##### ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

| CAS No    | Chemical name                              |                   |         |                     |                    |
|-----------|--------------------------------------------|-------------------|---------|---------------------|--------------------|
|           | Exposure route                             | Dose              | Species | Source              | Method             |
| 7085-85-0 | ethyl 2-cyanoacrylate                      |                   |         |                     |                    |
|           | oral                                       | LD50 > 5000 mg/kg | Rat     | Study report (1973) | OECD Guideline 423 |
|           | dermal                                     | LD50 > 2000 mg/kg | Rabbit  | Study report (1973) | OECD Guideline 402 |
| 123-31-9  | 1,4-dihydroxybenzene; hydroquinone; quinol |                   |         |                     |                    |
|           | oral                                       | LD50 302 mg/kg    | Rat     | IUCLID              |                    |

#### Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye irritation.

#### Sensitising effects

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 5634

Revision date: 21.03.2025

Product code: 5634

Page 8 of 12

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

#### STOT-single exposure

May cause respiratory irritation. (ethyl 2-cyanoacrylate)

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### Specific effects in experiment on an animal

No data available

#### Additional information on tests

No data available

#### Practical experience

May be harmful if swallowed, in contact with skin or if inhaled.

### 11.2. Information on other hazards

#### Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

## SECTION 12: Ecological information

### 12.1. Toxicity

Based on available data, the classification criteria are not met.

### 12.2. Persistence and degradability

No data available

| CAS No    | Chemical name         |       |   |        |
|-----------|-----------------------|-------|---|--------|
|           | Method                | Value | d | Source |
|           | Evaluation            |       |   |        |
| 7085-85-0 | ethyl 2-cyanoacrylate |       |   |        |
|           | OECD 301D             | 57%   |   |        |

### 12.3. Bioaccumulative potential

No data available

#### Partition coefficient n-octanol/water

| CAS No    | Chemical name         | Log Pow |
|-----------|-----------------------|---------|
| 7085-85-0 | ethyl 2-cyanoacrylate | 0,776   |

### 12.4. Mobility in soil

No further relevant information available.

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

### 12.7. Other adverse effects

No data available

#### Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 5634

Revision date: 21.03.2025

Product code: 5634

Page 9 of 12

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

#### List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

#### List of Wastes Code - used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

#### List of Wastes Code - contaminated packaging

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

#### Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

## SECTION 14: Transport information

### Land transport (ADR/RID)

|                                          |                                                          |
|------------------------------------------|----------------------------------------------------------|
| <u>14.1. UN number or ID number:</u>     | No dangerous good in sense of this transport regulation. |
| <u>14.2. UN proper shipping name:</u>    | No dangerous good in sense of this transport regulation. |
| <u>14.3. Transport hazard class(es):</u> | No dangerous good in sense of this transport regulation. |
| <u>14.4. Packing group:</u>              | No dangerous good in sense of this transport regulation. |

### Inland waterways transport (ADN)

|                                          |                                                          |
|------------------------------------------|----------------------------------------------------------|
| <u>14.1. UN number or ID number:</u>     | No dangerous good in sense of this transport regulation. |
| <u>14.2. UN proper shipping name:</u>    | No dangerous good in sense of this transport regulation. |
| <u>14.3. Transport hazard class(es):</u> | No dangerous good in sense of this transport regulation. |
| <u>14.4. Packing group:</u>              | No dangerous good in sense of this transport regulation. |

### Marine transport (IMDG)

|                                          |                                                          |
|------------------------------------------|----------------------------------------------------------|
| <u>14.1. UN number or ID number:</u>     | No dangerous good in sense of this transport regulation. |
| <u>14.2. UN proper shipping name:</u>    | No dangerous good in sense of this transport regulation. |
| <u>14.3. Transport hazard class(es):</u> | No dangerous good in sense of this transport regulation. |
| <u>14.4. Packing group:</u>              | No dangerous good in sense of this transport regulation. |

### Air transport (ICAO-TI/IATA-DGR)

|                                          |                                   |
|------------------------------------------|-----------------------------------|
| <u>14.1. UN number or ID number:</u>     | UN 3334                           |
| <u>14.2. UN proper shipping name:</u>    | AVIATION REGULATED LIQUID, N.O.S. |
| <u>14.3. Transport hazard class(es):</u> | 9                                 |
| <u>14.4. Packing group:</u>              | III                               |
| Hazard label:                            | 9                                 |

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 5634

Revision date: 21.03.2025

Product code: 5634

Page 10 of 12



|                                        |         |       |
|----------------------------------------|---------|-------|
| Special Provisions:                    | A27     |       |
| Limited quantity Passenger:            | 30 kg G |       |
| Passenger LQ:                          | Y964    |       |
| Excepted quantity:                     | E1      |       |
| IATA-packing instructions - Passenger: |         | 964   |
| IATA-max. quantity - Passenger:        |         | 450 L |
| IATA-packing instructions - Cargo:     |         | 964   |
| IATA-max. quantity - Cargo:            |         | 450 L |

#### Other applicable information (air transport)

A27: Primary packs containing not more than 500ml are unregulated by this mode of transport and may be shipped unrestricted.

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

#### 14.6. Special precautions for user

No information available.

#### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

Information according to Directive 2012/18/EU (SEVESO III):

Not subject to 2012/18/EU (SEVESO III)

##### National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D):

2 - obviously hazardous to water

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

**Kisling - 5634**

Revision date: 21.03.2025

Product code: 5634

Page 11 of 12

### Abbreviations and acronyms

Acute Tox: Acute toxicity  
 Skin Irrit: Skin irritation  
 Eye Dam: Eye damage  
 Eye Irrit: Eye irritation  
 Skin Sens: Skin sensitisation  
 Muta: Germ cell mutagenicity  
 Carc: Carcinogenicity  
 STOT SE: Specific target organ toxicity - single exposure  
 Aquatic Acute: Acute aquatic hazard  
 Aquatic Chronic: Chronic aquatic hazard  
 CLP: Classification, labelling and Packaging  
 REACH: Registration, Evaluation and Authorization of Chemicals  
 GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals  
 UN: United Nations  
 CAS: Chemical Abstracts Service  
 DNEL: Derived No Effect Level  
 DMEL: Derived Minimal Effect Level  
 PNEC: Predicted No Effect Concentration  
 ATE: Acute toxicity estimate  
 LC50: Lethal concentration, 50%  
 LD50: Lethal dose, 50%  
 LL50: Lethal loading, 50%  
 EL50: Effect loading, 50%  
 EC50: Effective Concentration 50%  
 ErC50: Effective Concentration 50%, growth rate  
 NOEC: No Observed Effect Concentration  
 BCF: Bio-concentration factor  
 PBT: persistent, bioaccumulative, toxic  
 vPvB: very persistent, very bioaccumulative  
 ADR: Accord européen sur le transport des marchandises dangereuses par Route  
 (European Agreement concerning the International Carriage of Dangerous Goods by Road )  
 RID: Regulations concerning the international carriage of dangerous goods by rail  
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
 (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation  
 intérieures)  
 IMDG: International Maritime Code for Dangerous Goods  
 EmS: Emergency Schedules  
 MFAG: Medical First Aid Guide  
 IATA: International Air Transport Association  
 ICAO: International Civil Aviation Organization  
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships  
 IBC: Intermediate Bulk Container  
 VOC: Volatile Organic Compounds  
 SVHC: Substance of Very High Concern  
 For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety  
 assessment, chapter R.20 (Table of terms and abbreviations).

### Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

| Classification      | Classification procedure |
|---------------------|--------------------------|
| Skin Irrit. 2; H315 | Calculation method       |
| Eye Irrit. 2; H319  | Calculation method       |
| STOT SE 3; H335     | Calculation method       |

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 5634

Revision date: 21.03.2025

Product code: 5634

Page 12 of 12

#### Relevant H and EUH statements (number and full text)

|        |                                                                                           |
|--------|-------------------------------------------------------------------------------------------|
| H302   | Harmful if swallowed.                                                                     |
| H315   | Causes skin irritation.                                                                   |
| H317   | May cause an allergic skin reaction.                                                      |
| H318   | Causes serious eye damage.                                                                |
| H319   | Causes serious eye irritation.                                                            |
| H335   | May cause respiratory irritation.                                                         |
| H341   | Suspected of causing genetic defects.                                                     |
| H351   | Suspected of causing cancer.                                                              |
| H400   | Very toxic to aquatic life.                                                               |
| H410   | Very toxic to aquatic life with long lasting effects.                                     |
| EUH202 | Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children. |

#### Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

---

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*